





**Propojovací svorka 16-120mm<sup>2</sup>, pro 5 mm**


**Typ** AKU120/5  
**Catalog No.** 107190

**Dodavatelský program**


Sortiment			60mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	17 x 15
Šířka		mm	23.5
Jmenovitý proud	le	a	440
Vodič			16 - 120 mm <sup>2</sup> AWG 4 - MCM 250. přímo svorkovaná:   # 4 x 16 x 0,8 mm nebo 6 x 16 x 0,8 mm nebo 10 x 16 x 0,8 mm
Použitelné pro			All 5 mm thick flat busbars

**Upozornění**

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

# CU band

 CU busbar

**aprobace,**

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

