








Propojovací svorka 16-70mm<sup>2</sup>, pro 5 mm

Typ **AKU70/5**  
 Catalog No. **107189**

**Dodavatelský program**

Sortiment			60mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	14 x 14
Šířka		mm	20.5
Jmenovitý proud	le	a	400
Vodič			16 - 70 mm <sup>2</sup> AWG 4 - AWG 2/0. přímo svorkovaná:   # 2x (3 x 9 x 0,8 mm) nebo 6 x 9 x 0,8 mm
Použitelné pro			All 5 mm thick flat busbars
<b>Upozornění</b>			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

**aprobace,**

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

