








Propojovací svorka 1.5-16mm², pro 5 mm

Typ AKU16/5
Catalog No. 107187

Dodavatelský program

Sortiment			60mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	7.5 x 7.5
Šířka		mm	11.5
Jmenovitý proud	le	a	180
Vodič			1,5 - 16 mm ² AWG 14 - AWG 6. přímo svorkovaná:    # 8 x 6 x 0,5 mm
Použitelné pro			All 5 mm thick flat busbars
Upozornění			
 round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

