






Propojovací svorka 16-120mm², 10 mm

Typ AKU120/10
Catalog No. 107194

Dodavatelský program

Sortiment			60mm systém 185mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	17 x 15
Šířka		mm	23.5
Jmenovitý proud	I _e	a	440
Vodič			16 - 120 mm ² AWG 4 - MCM 250. přímo svorkovaná:   # 4 x 16 x 0,8 mm nebo 6 x 16 x 0,8 mm nebo 10 x 16 x 0,8 mm
Použitelné pro			All 10 mm thick flat busbars
Upozornění			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

