



Propojovací svorka 16-70mm², 10 mm


Typ AKU70/10
Catalog No. 107193

Dodavatelský program


Sortiment			60mm systém 185mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	14 x 14
Šířka		mm	20.5
Jmenovitý proud	le	a	400
Vodič			16 - 70 mm ² AWG 4 - AWG 2/0. přímo svorkovaná:   # 2x (3 x 9 x 0,8 mm) nebo 6 x 9 x 0,8 mm
Použitelné pro			All 10 mm thick flat busbars

Upozornění

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

CU band

 CU busbar

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

