



Pomocný kontakt, 1W, 2A, 250VAC, 0.5HP

Typ **ASAUXSC-SPM**
Catalog No. **131785**

Dodavatelský program

Sortiment		Příslušenství
Výrobky		Pomocný kontakt
Oblast použití		Obytná budova Průmyslová budova Volné plochy
Použitelný pro		SPMT2PA

Technická data podle ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalací zařízení, přístroj / Komponenta ochranného snímace / Pomocný kontakt, signalizační kontakt (ecI@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Other
Additional equipment		Auxiliary switch
Attached at delivery		No
Assembly width (TE)		0.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		1
Number of fault-signal switches		0
Rated switch current	A	2
Rated voltage	V	250
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0