



Přednostní relé, 250VAC, 1R, 15-32A, 1HP

Typ **Z-LAR32-0**
Catalog No. **248258**

Technická data podle ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Load shedding relay for distribution board (EC001655)			
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Modulární radový vestavený přístroj pro rozbočovací proudových okruhu / Load shedding relay for distribution board (ecl@ss10.0.1-27-14-23-32 [ACN383011])			
Rated voltage	V		250
Rated current I _u	A		15 - 32
Just-operate current	A		15 - 32
Max. time-delayed switch-off	ms		0
Max. continuous current	A		32
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Rated current (control contacts)	A		1
Max. switching voltage (control contacts)	V		250
Max. switching power (control contacts)	VA		7.36
Electrical lifespan (control contacts)	c (contacts)		100000
Mechanical lifetime (control contacts)	c (contacts)		0
Max. electrical switching cycles	c/h		3600
Voltage type			AC
Mounting method			DIN rail
Width in number of modular spacings			1
Built-in depth	mm		60
Degree of protection (IP)			IP20