

DATOVÝ LIST - AKS300



Rozpěrná svorka 150-300mm², pro 20x5-30x10

Typ
Catalog No. **AKS300**
107196



Dodavatelský program

Sortiment			60mm systém 185mm systém
Základní funkce			Svorky
Dílčí sortiment			Rozpěrné svorky
Popis			Připojení ke sběrnicím bez vrtání děr Propojení kontaktů kabelů a propojovací lišty probíhá přes lože kabelu
Šířka		mm	41
Jmenovitý proud	I _e	A	600
Vodič			95 - 300 mm ² MCM300 - MCM600. přímo svorkovaná:   
Cu factor		kg	0,00
Použitelný pro			20 x 5/10 25 x 5/10 30 x 5/10
Použitelné pro			Double T profile
Upozornění  round conductor, solid  Flexible, round conductor with correctly crimped ferrule Round conductor, stranded  Section conductor, solid Sector conductor, stranded # CU band  CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

