

## Cable glands Progress® nickel-plated brass



### Long entry thread Pg

#### Type approval: Progress MS

- Two-piece sealing insert
- not overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Order number:</b>               | <b>1100.13</b>               |
| EAN:                               | 7611614106144                |
| Material                           | Nickel-plated brass          |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating                   | 4X                           |
| Entry thread                       | Pg 13                        |
| Clamping range with insert min.    | 8.0 mm                       |
| Clamping range with insert max.    | 11.0 mm                      |
| Clamping range without insert min. | 11.0 mm                      |
| Clamping range without insert max. | 15.0 mm                      |
| Wrench size                        | 24 mm                        |
| Dimension H                        | 23 mm                        |
| Thread length L                    | 10 mm                        |
| UL - clamping range                | 10.6-11.0 mm                 |
| Dispatch                           | 50                           |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.