



Bezšroubová svorkovnice 1xN pro KLV, 1x2,5-25mm² a 7x0,5-4mm² (N)

Typ **KSK-N**
Catalog No. **178903**

Dodavatelský program

Základní funkce		Informace k příslušenství
Accessories		General
Product range		KLV DB0
Stupeň krytí		IP2X

Technická data podle ETIM 7.0

Terminal blocks (EG000012) / Single- and multi-pole terminal strip (EC001284)			
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Svorka (mimo venkovní vedení) / Svorková lišta jedno a vícepólová (ecI@ss10.0.1-27-14-11-06 [AAB921016])			
Drill hole distance centrically	mm	1	
Explosion-tested version 'Ex e'		No	
Connectable conductor cross section fine-strand without cable end sleeve	mm ²	2.5 - 25	
Connectable conductor cross section fine-strand with cable end sleeve	mm ²	2.5 - 16	
Connectable conductor cross section solid-core	mm ²	2.5 - 25	
Connectable conductor cross section multi-wired	mm ²	2.5 - 25	
Rated current I _n	A	63	
Rated voltage	V	400	
Type of electrical connection 1		Screw connection	
Type of electrical connection 2		Plug-in connection	
Connection position		Inclined	
Number of poles		1	
Number of clamp positions per pole		8	
Mounting method		Direct mounting	
Material insulation body		Thermoplastic	
Operation temperature	°C	35 - 35	
Inflammability class of insulation material acc. with UL94		V0	
Width/grid dimension	mm	55	
Height at lowest possible mounting height	mm	17	
Length	mm	19.5	
Closing plate required		No	
Colour		Blue	
Transparent		No	