


128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex Tel: 33(0)5 55 06 87 87 - Fax: 33(0)5 55 06 88 88 www.legrand.com




1. USE

For recharging portable devices such as phones, smartphones, tablets, MP3 or MP4 players, loudspeakers, watches, game consoles, powerbanks.

Designation	White
Double USB socket 5 V≕ - 3.0 A	2 785 94L

3. DIMENSIONS (mm)



45

Λ	CO	NIN	ECT	ION
- 4 .	CO		ECI	ION

45

Type of terminals: with screws Terminal capacity: 2 x 2.5 mm² Stripping length: 6 mm Screwdriver: flat 3.5 mm

Circuit breaker: 16 A MAXI

Necessary safety precautions:



Switch OFF the power at the main circuit breaker. Make sure that the power is OFF besfore continuing with the installation.

42

8.5

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Impact tests: IK 04 Penetration by solid bodies/liquid: IP 40

■ 5.2 Material characteristics

Base: PC V-0 class Cover-plate: ABS White RAL 9003

Self-extinguishing:

 850° C/30 s for insulating parts holding live parts in place. 650° C/30 s for other parts made of insulating materials.

■ 5.3 Electrical characteristics

All values listed below are measured at an ambient temperature of $+ 20^{\circ}$ and after 30 minutes of operation.

Nominal input voltage	100-240 V~		
Nominal input frequency	50/60 Hz		
Nominal output voltage	5.0 V		
Nominal input current	0.3 A		
Maximum output current	3.0 A		
Power consumption	15.0 W		
Average efficiency in active mode	84.43 %		
Stand-by power consumption	< 0.07 W		
Consumption class without load and average level of efficiency: Level VI*			
Protection class	ll - Low voltage		

*NB: European Regulation No. 278/2009 of 6 April 2009, Directive 2005/125/EC on eco-design requirements for AC/DC power supplies.

Note: To optimize the charging time of your device, ensure turn it off during the charging phase.

■ 5.4 Climate characteristics

Storage temperature: - 20° C to + 70° C Operating temperature: 0° C to + 40° C

6. CLEANING

Surface cleaning with a cloth. Do not use: acetone, tar remover, trichlorethylene.

Caution: Always test before using other special cleaning products.

7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e-catalogue.