LED outdoor light without sensor

L 42 C

without motion detector, with Bluetooth EAN 4007841 085254 Article number 085254









3000 K















30 years (Ø 4,5h / day)

IP54

3000K warm-white

connectable v bluetooth

10 - 100% main ligi brightness

Settings via App

utdoor light

ontrol gear not exchangeable

exchangeable

plastic free packaging

Function description

Upright house lighting. The robust L 42 C wall light without a sensor in an elegant aluminium housing features a warm white 3000 K hue and uses the long-life STEINEL LED system. Commissioning, setting up and networking via the Bluetooth Mesh combined with the free STEINEL app. Featuring a soft light start, main light and neighbouring group function. Delivered in plastic-free packaging.

Technical specifications

Dimensions (L x W x H)	105 x 131 x 274 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	Connect Bluetooth Mesh
With remote control	No
Version	without motion detector, with Bluetooth
PU1, EAN	4007841085254
Application, place	Outdoors
Application, room	outdoors, front door, all round the building, terrace / balcony
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Installation site	wall
Impact resistance	IK03
IP-rating	IP54
Protection class	I

Housing material	Aluminium
Cover material	Plastic, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	12,6 W
Average rated life expectancy of power supply unit at 25°C	> 60000 h
Abdeckmaterial Lieferumfang	Cover clips
Luminous flux total product	990 lm
Measured luminos flux (360°)	990 lm
Colour temperature	3000 K
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Continuous light	selectable
Main light adjustable	0 - 100 %
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	Bluetooth Mesh Connect

LED outdoor light without sensor

L 42 C

without motion detector, with Bluetooth EAN 4007841 085254 Article number 085254





Technical specifications

Ambient temperature

-20 - 40 °C

Dimension Drawing





Circuit diagram Bluetooth



Circuit diagram Bluetooth

